

Home >> Commercial Products >> Rolling Service >> 616

Rolling Service 616



The 615 and 616 Series rolling service doors offer an attractive, durable option to fit door openings up to 16' wide and 16' high (4877mm and 4877). The 615 and 616 Series are differentiated by their slat profiles and weatherseal

[Privacy](#)

[Legal](#)

options. The 615 Series is offered with curved slats and vinyl weatherstripping on the bottom bar. The flat-slat 616 Series, with weatherstripping on the bottom, exterior curtain-side guides and internal hood, is better suited for applications where minimizing air infiltration is a consideration.

Standard Features At a Glance

Max. standard width	16' (4877 mm)
Max. standard width	16' (4877 mm)
Max. standard height	16' (4877 mm)
Curtain	24 ga. galvanized steel
Slat profile	Flat, type F-265 (616 Series)
Finish	Gray or tan
Hood	24 ga. galvanized steel
Windload	20 psf
Standard mounting	Face of wall
Operation	Manual push-up up to 108 sq. ft. (10,034 sq.mm) or 12' x 9' (3658 mm x 2743 mm) Chain hoist over 108 sq. ft. (10,034 sq.mm) or 12' x 9' (3658 mm x 2743 mm)2743 x mm (3658>
Standard springs	20,000 cycle
Weatherseals	Bottom, exterior side guide and internal hood baffle (616 Series)
Guides	Galvanized steel roll-formed shapes
Bottom bar	Extruded aluminum with weatherseal

Lock	Interior slide bolt on push-up Chain keepers on chain hoist
Warranty	15-month limited

Options

- Electric operator
- Bottom sensing edge
- Between-jambs mounting
- Galvanized steel bottom bar and guides
- Cylinder lock
- Powder-coat paint finish in 197 standard colors, or color-matched to specification